

Building 90, SEME, Budds Lane, Bordon, Hampshire GU35 OJE Email: sales@polymax.co.uk Tel: 01420 474123 Web: www.polymax.co.uk

## Technical Data Sheet

Compound: EP70 - EPDM (Ethylene Propylene Diene Monomer)

Colour: Black

Complies with: ASTM D2000 M2BA710 A14 B13 F19

|  |  | <u>Required</u>        | <u>Tested</u>           |
|--|--|------------------------|-------------------------|
| Mechanical Propertie Shore Hardness (Sh.A) Tensile Strength (MPa) Elongation at Break (9 Specific Gravity: | <del>.</del><br>:<br>):  | 70<br>10<br>250<br>n/a | 71<br>14<br>385<br>1.19 |
| <u>Thermal Properties</u> Operating Temperature Range (°C):  |  | n/a                    | - 45to +145             |
| Compression Set Test @ 70°C for 22 Hours (%):  |  | 25                     | 13                      |
| Heat Resistance Test (   | <ul><li>100°C X 70 Hours</li><li>Hardness Change Points:</li><li>Tensile Strength Change (%):</li><li>Elongation Change (%):</li></ul> | ± 15<br>± 30<br>- 50   | +3<br>+1<br>-9          |
| Low Temperature Brittleness Test @ -55°C X 3 Min   |  | Pass                   | Not Brittle             |